# UTILITY SERVICE CO., INC.

1230 Peachtree St NE, Suite 1100 - Promenade · Atlanta, GA 30309 Toll-free: 855-526-4413 | Fax: 478-987-2991

utilityservice.com

Date: 25 July 2016

Submitted by: M. Montgomery

Local Phone: 612-816-3235

SFID: 45075

CN:

SO:

Proposal Submitted To:			Phone Number:	F	ax Number:
Blaine, MN			763-785-6137		
Street Address:			Description of Work to be Performed:		
1801 101st Ave NE			Ice Pigging P	otable Water Main	ıs - 5-year plan
City: State: Zip Code:		Zip Code:	County/Parish:	· · · · · · · · · · · · · · · · · · ·	
Blaine	MN	55449	3192		
Accounts Payable Contact Name:	Email:		Job Site Address:	**************************************	
Mr. George Linngren	glinngren@	gci.blaine.mn.us	5 year plan		
Job Contact (Inspection Reports): Email:		Length (FT):	Size (Inches):	Material:	
Mr. George Linngren glinngren@ci.blaine.mn.us		TBD	Various	Various	

Utility Service Co., Inc. agrees to provide all labor, equipment, and materials needed to complete the following:

- 1. This service agreement will be for a 5-year term with an annual expense of \$100,000/year.
- 2. Prior to work being completed the City of Blaine, MN shall provide maps highlighting a prioritized section of the water network for each SOW.
- 3. The Utility Service Co. Inc. Product Manager shall propose a schedule of ice pigging runs based on the prioritized map provided.
- 4. Each year, Utility Service Co. Inc. shall provide the equivalent of 2,700 gallons of ice, per day for water main cleaning.
- 5. Each project shall consist of minimum of 7 days of pigging.
- 6. Each day shall be billed at the discounted rate of \$10,000 per day.
- 7. Each mobilization shall be charged at a rate of \$10,000 per mobilization.

Please sign and date this proposal and fax one copy to our office.

Five Hundred Thousand and	00/100	Dollars \$500,000.00
Payment to be made as follows: Payment in Full Completion	n of Work – plus a	Il applicable taxes
Remittance Address: Utility Service Co	o., Inc., P O Box	x 674233, Dallas, TX 75267-4233
All material is guaranteed to be as specified. All work to be completed in a substantial workmanlike manner according to specifications submitted, per standard practices. Any alteration or deviation from above specifications involving extra costs will be executed only upon written orders, and will become an extra charge over and above the estimate. All agreements contingent upon strikes, accidents or delays beyond our control. Owner to carry fire, tornado and other necessary insurance. Our workers are fully covered by Workmen's Compensation Insurance.	Authorized USG Signature Note:	This proposal may be withdrawn by us if not accepted within Sixty (60) days.
Acceptance of Proposal - The above prices, specifications and conditions are conditionally specified. Payment will be made as outlined above.	ons are satisfactory an	nd are hereby accepted. You are authorized to do the work as
Fiscal Yr Beginning Month	Signature	
Date of Acceptance	Printed Name	



### UTILITY SERVICE CO., INC.

1230 Peachtree St NE, Suite 1100 - Promenade · Atlanta, GA 30309 Toll-free: 855-526-4413 | Fax: 478-987-2991 utilityservice.com

- 8. Owner agrees to provide the following:
  - a. All potable water necessary to create the ice slurry,
  - b. Secure location to store the ice making equipment,
  - c. Network Operators to isolate and re-open valves and hydrants during the project,
  - d. MOT (Maintenance of Traffic) procedures in accordance with the requirements written in The Manual of Uniform Traffic Devices.
  - e. A tanker truck to haul the wastes where a sanitary sewer is not in close proximity. Note: The discharge should not be to ground unless specific State approval is acquired.
  - f. Exercise all relevant valves and hydrants and test for operational working order.
  - g. A complete isolation of the main on the day of operation.
- 9. USCI shall provide a report summarizing the daily cleaning events, water quality pre and post cleaning, and a quantitative amount of sediments removed only on those lines where a connection can be made to the discharge point.
- 10. USCI shall endeavor to manage the ice concentration to maximize cleaning efficiency and minimize the removal of tuberculation that could cause future water quality complaints.
- 11. Owner agrees that there is considerable expense to produce 2,700 gallons of ice slurry and that the ice slurry cannot be held for more than 12 hours before it becomes unusable. If on a scheduled work day, Owner cannot isolate the water main or does not have the needed personnel, USCI shall charge the Owner the Discounted Daily Rate of \$10,000 per day.
- 12. USCI shall not charge Owner the above-mentioned Daily Rate, if USCI cannot perform the complete day's work due to those factors under USCI's control, i.e. the ice is not in suitable condition, USCI cannot provide the necessary labor, equipment failure, etc.
- 13. Due to the potential condition or deterioration of assets that may or may not have been maintained, Owner shall indemnify USCI, and all officers and agents of USCI, against all damages, costs or expenses that may result from damage to property or personal injury caused by reason of the Owner's failure to maintain its assets or deterioration of Owner's assets in relation to any work in connection with this Agreement. Such indemnity includes, but is not limited to, damage to property or personal injury occasioned by any negligence, act or omission to act by USCI or any of its servants, agents, employees, or any subcontractor retained by USCI to perform any of the work contemplated by or under this agreement.
- 14. Once delivered to the job site, ownership of the ice slurry is transferred to Owner. All ice delivered to and removed from the water main, along with the wastes generated from the resulting process shall be the sole property of Owner. Owner shall dictate the specific disposal procedures to be employed during the process.



# UTILITY SERVICE CO., INC.

1230 Peachtree St NE, Suite 1100 - Promenade · Atlanta, GA 30309

Toll-free: 855-526-4413 | Fax: 478-987-2991 utilityservice.com

Blaine, MN / 5 year plan

4	۷	2
	Ł	_
	6	5
	į,	-
ij	<	S
ij		9
1	4	100
	C	)
	Q	y
	7	=
	=	2
1	ζ	5
	0	J
	ē	-
	7	5
m	1	1
2	v	,
	7	3
	ñ	í
	7	ž
	ž	÷
	5	2
	2	2
	C	5
	Š	

TBC

©2016 Utility Service Co., Inc.

CONFIDENTIAL - Pg 3



# UTILITY SERVICE CO., INC.

1230 Peachtree St NE, Suite 1100 - Promenade · Atlanta, GA 30309 Toll-free: 855-526-4413 | Fax: 478-987-2991 utilityservice.com

Responsi	bility	Ice Making Procedure
Owner	1.	The ice delivery unit and ice making unit shall be staged in a suitable level area, preferably a fenced area at a water treatment plant or other facility. The facility needs access to potable water, preferably a hydrant but also a water spigot will work.
USCI	2.	The hoses and fittings connecting the ice maker and delivery unit shall be disinfected and connected. This connection makes a closed loop system between the ice maker and delivery unit. The only place for contaminates to enter the system are through the tank hatch which shall be closed except for visual inspection by the operator.
USCI	3.	Approximately 2,700 gallons of potable water shall be added to the delivery tank, along with approximately 1100lbs of NSF-60 Certified Sodium Chloride.
USCI	4.	If requested by the Owner, the Chlorine residual in the brine solution may be increased to 10ppm. The chlorine residual shall be tested, and then the appropriate amount of NSF-60 Certified Sodium hypochlorite shall be added to the brine solution. The solution shall be retested to confirm the chlorine residual.
USCI	5.	The PLC controlling the ice making process shall be started and allowed to run overnight. USCI shall monitor the procedure overnight via periodic visits or remote monitoring.
USCI	6.	After completion of the ice making process, the delivery pump shall be started and a small amount of ice shall be tested to determine the ice fraction. If the ice fraction is below the project's requirement, the ice making process shall continue.
USCI	7.	If the ice fraction is in accordance with the project's requirement, then the ice maker shall be shut off and disconnected. The ice contained in the delivery unit shall be delivered to the job site.



# UTILITY SERVICE CO., INC.

1230 Peachtree St NE, Suite 1100 - Promenade · Atlanta, GA 30309 Toll-free: 855-526-4413 | Fax: 478-987-2991 utilityservice.com

Responsi	ibility	On-Site Delivery Actions		
Owner	1.	Owner shall setup and maintain traffic control procedures in conjunction with the setup procedures listed in Steps 2-3.		
USCI	2.	<ul> <li>The ice pigging delivery unit shall be parked near the insertion fitting.</li> <li>Hoses shall be setup from the delivery unit to the insertion point.</li> <li>The insertion point shall be flushed to clean out the barrel, and then shut off.</li> <li>The insertion point fittings shall be disinfected with 250ppm Cl solution.</li> <li>The hoses shall be connected to the insertion point.</li> </ul>		
USCI	3.	<ul> <li>Where possible, the extraction point instrumentation unit shall be setup near the extraction hydrant.</li> <li>Hoses shall be setup from the instrumentation unit to the hydrant.</li> <li>Hoses shall run from the instrumentation unit to the sanitary sewer.</li> <li>De-chlorination equipment shall be setup where required.</li> <li>The hydrant shall be flushed to clean out the barrel, then shut off</li> <li>The hydrant fittings shall be disinfected with 250ppm Cl solution.</li> <li>The instrumentation unit connected to the hydrant, and the hydrant turned on.</li> <li>Water quality readings shall be taken.</li> <li>The unit shall be allowed to flow water.</li> </ul>		
Owner	4.	The final valves shall be closed to isolate the water main.		
USCI	5.	The isolation of the main shall be verified by the instrumentation unit. The extraction hydrant valve shall be closed after main isolation is verified and before the pressure goes below 20psi in the main.		
USCI	6.	The insertion point valve shall be opened and the ice slurry pumped into the water main.  • Prior to pumping the percent solids of the ice slurry shall be documented.  The extraction hydrant valve shall be operated to allow for the displacement of water by the introduction of the ice and maintain the pressure above 20psi in the main.		
USCI	7.	Once the proper amount of ice slurry has been delivered, the insertion point and extraction hydrant valve shall be closed and the pressure is maintained above 20psi in the main.		



# UTILITY SERVICE CO., INC.

1230 Peachtree St NE, Suite 1100 - Promenade · Atlanta, GA 30309 Toll-free: 855-526-4413 | Fax: 478-987-2991 utilityservice.com

instrumentation unit, the operator shall open the extraction hydrant valve to control the flow of water and monitor the progress of the ice pig.  USCI  10. Once the pig is monitored to arrive, the flow of water shall be diverted from the dechlorination equipment to flow to the sanitary sewer specified by the Owner.  USCI  11. The water quality shall be monitored and flow shall continue until the water quality returns to the initial water quality readings.  • Final chlorine shall be documented.  USCI  12. The insertion point shall be flushed to remove any ice that remains between the water main and hydrant.			
instrumentation unit, the operator shall open the extraction hydrant valve to control the flow of water and monitor the progress of the ice pig.  USCI  10. Once the pig is monitored to arrive, the flow of water shall be diverted from the dechlorination equipment to flow to the sanitary sewer specified by the Owner.  USCI  11. The water quality shall be monitored and flow shall continue until the water quality returns to the initial water quality readings.  • Final chlorine shall be documented.  USCI  12. The insertion point shall be flushed to remove any ice that remains between the water main and hydrant.  USCI  13. The entrance and exit locations shall be cleaned up with all materials and equipment removed from the site.	Owner	8.	
chlorination equipment to flow to the sanitary sewer specified by the Owner.  11. The water quality shall be monitored and flow shall continue until the water quality returns to the initial water quality readings.  • Final chlorine shall be documented.  USCI  12. The insertion point shall be flushed to remove any ice that remains between the water main and hydrant.  USCI  13. The entrance and exit locations shall be cleaned up with all materials and equipment removed from the site.	USCI	9.	Once full system pressure, as observed prior to system shutdown, is monitored at the instrumentation unit, the operator shall open the extraction hydrant valve to control the flow of water and monitor the progress of the ice pig.
returns to the initial water quality readings.  • Final chlorine shall be documented.  USCI  12. The insertion point shall be flushed to remove any ice that remains between the water main and hydrant.  USCI  13. The entrance and exit locations shall be cleaned up with all materials and equipment removed from the site.	USCI	10.	Once the pig is monitored to arrive, the flow of water shall be diverted from the de- chlorination equipment to flow to the sanitary sewer specified by the Owner.
USCI  13. The entrance and exit locations shall be cleaned up with all materials and equipmen removed from the site.	USCI	11.	
removed from the site.	USCI	12.	
Owner 14. The downstream main valve shall be opened and returned to full service.	USCI	13.	The entrance and exit locations shall be cleaned up with all materials and equipment removed from the site.
	Owner	14.	The downstream main valve shall be opened and returned to full service.